



Oiled Floor Care [eco]

Care product for oiled and waxed wooden floors




Availability	
Quantity per pallet	288
Size / Quantity	4 x 1 l
Type of container	Plastic bottle
Container code	01
Art. no.	
7699	■

Application rate 200 ml per 10 l of cleaning water



Range of use



- Interior wood
- Wooden floors and stairs
- Cork floors
- To be used only on previously treated surfaces (e.g. with Hard Wax Oil, Hard Wax Oil [eco], HWS-112 & HSO-118 [eco]).

Property profile



- Made from at least 90% renewable raw materials
- Forms a thin protective layer of high quality waxes on the surface
- Protects the surface from early wear
- Can be polished after drying

Characteristic data of the product

Binder	Natural & synthetic waxes
Density (20 °C)	Approx. 0.99 g/cm ³
Odour	Mild

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Certificates

- DIN EN 71-3 "Migration of certain elements"

Additional information

- [Data sheet for constituents](#)
- [Care instructions for oiled surfaces and floors](#)

Possible system products

- [Hard Wax Oil \(0695\)](#)
- [Natural Hard Wax Oil \[eco\] \(7684\)](#)
- [HSO-118 High Solid Oil \[eco\] \(7708\)](#)
- [HWS-112 Hard Wax Seal \(1826\)](#)
- [Aqua HWS-712 Hard Wax Seal \[eco\] \(5290\)](#)


Preparation

- Substrate preparation
The substrate must be clean, dust-free and dry.



Directions

Shake well before use.
Damp-wipe the floor.



Tips on use

Dust and loose dirt on floors and stairs should be removed regularly using a soft broom or mop.
Never flood wood floors since this can cause damage due to swelling of the wood.
To avoid stains, never leave damp cloths on wood surfaces.

- Thinning
Dilute the concentrate with water.

Notes


DIN EN 71-3 "Migration of certain elements":
This product complies with the limits for the migration of heavy metals to children's toys according to DIN EN 71-3 and thus fulfils one of several further requirements for the safety of children's toys according to the EU "Toy Directive" (2009/48/EC).
Observe the "Care instructions for oiled surfaces and floors".

Tools / Cleaning

Cloth

Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.
Use the contents of open containers as quickly as possible.



Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Detergents Regulation (EC) No 648/2004

< 5% methylchloroisothiazolinone/methylisothiazolinone (3:1), benzisothiazolinone

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.