



## Care & Maintenance Kit

For oiled surfaces


Availability	
Quantity per pallet	245
Size / Quantity	
Type of container	Set in carton
Container code	01
Art. no.	
7739	■
The kit contains: 1 abrasive cloth, 1 container opener, 250 ml cleaning agent, 375 ml Hard Wax Oil clear, 2 special cloths, and care and maintenance instructions	

### Application rate

5 - 10 ml/m<sup>2</sup> per coat  
The application rate depends heavily on the absorbency of the wood



### Range of use



- Wooden stairs
- Interior wood
- High-quality solid wood furniture
- Panels and moulding

### Property profile



- Penetrates deeply and emphasises the natural texture of the wood
- Slight change in the gloss level of the treated surface
- Regular use increases the time between maintenance intervals and extends the lifespan of the surfaces
- Long-lasting, dirt-repelling and hard-wearing
- Forms a thin protective layer of high quality waxes on the surface
- Repels dust and dirt for easy-care surfaces

### Characteristic data of the product


Binder	Alkyd resin
Density (20 °C)	Approx. 1.01 g/cm <sup>3</sup> (cleaning agent) Approx. 0.85 g/cm <sup>3</sup> (Hard Wax Oil, clear)
Runout time s in DIN 4 cup	12 - 14
Odour	Characteristic

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

### Certificates

- [Pflege von geölten Flächen](#)
- [Pflege von geölten oder mit Hartwachssiegeln behandelten Oberflächen und Böden](#)

### Directions



- Conditions for use  
Temperature of the material, air and substrate: from min. +15 °C to max. +25 °C.

If necessary, soak cotton cloth with cleaner and wipe the surface in the direction of the grain; avoid intensive rubbing on the surface.  
Afterwards, wipe dry with a cotton cloth.  
In cases of stubborn dirt, water marks and light scratches, rub the surface with the abrasive pad included in the kit in the direction of the grain until a uniform wood surface is achieved. Then remove dust from the treated surface. Work in clear Hard Wax Oil evenly with the 2nd special cloth.  
The entire surface should be wiped once from visible edge to visible edge.  
Leave to dry for approx. 30 minutes.  
Shake well before use.  
Remove any excess material after approx. 20-30 minutes.



Tips on use



Please do not use any solvent-based products, microfibre cloths, scouring agents, aggressive cleaning agents or steam cleaners, as they will damage the surface.

Do not use on areas directly exposed to sunlight or on heated surfaces.

Any material that is not made of wood (e.g. covers, glass, door handles) must not come into contact with the cleaning product. If contact does occur, the material should be rinsed carefully with water.

**Risk of spontaneous ignition (DGUV Information 209-046). Do not use in the same workplace as NC-based varnishes or stains. Collect contaminated textiles (e.g. cleaning cloths, work clothing, dust bags) in fireproof waste containers and dispose of in a fireproof manner (under water).**

Ensure good ventilation.

■ Drying

After approx. 30 minutes

Treat the surface with care over the following days.

The coating may take significantly longer to dry thoroughly in lower temperatures, at high humidity or if the maximum layer thickness has been exceeded.

Practice values at +20 °C and 65% relative humidity.

■ Thinning

Ready to use


Tools / Cleaning

Lint-free cotton cloth



Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.



Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Detergents Regulation (EC) No 648/2004

<5% non-ionic surfactants, benzisothiazolinone, reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)

VOC content as per the "Decopaint" Directive (2004/42/EC)

Hard Wax Oil clear:  
EU limit value for the product (cat A/f): max. 700 g/l (2010).  
This product contains < 700 g/l VOC.



Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.