



# Anti-Slip Additive

Polymer granules



Type/Name	Availability	
	Quantity per pallet	480
	<b>Size / Quantity</b>	<b>0,25 kg</b>
	Type of container	Plastic box
	Container code	83
	<b>Art. no.</b>	
Anti-Slip Additive 150	7765	■
Anti-Slip Additive 250	7766	■

**Application rate** 2.5% based on the binder used, i.e. 125 g (half container) for a 5 kg container of 2K epoxy primer / 2K floor coating

**Range of use** ■ Polymer granules for producing slip-resistant sealants

**Property profile**

- Colour-neutral
- Easy to mix in
- Abrasion resistant

Characteristic data of the product	Grain density	1.1 g/cm <sup>3</sup>
	Particle size	Anti-Slip Additive 150: approx. 0.15 mm, Anti-Slip Additive 250: approx. 0.25 mm

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

### Production of the mixture

For guaranteed slip resistance and uniform grain distribution, the anti-slip additive must be stirred into the primer as well as the top coat. Before mixing, add the granules to component A of the Remmers 2K epoxy primer or 2K floor coating. Then mix intensively with a suitable mixer and mixing paddle until no more streaks are visible. A minimum mixing time of 2-3 minutes must be observed. Pour the premixed material into an additional container (e.g. clean paint bucket) and mix again briefly.

**Directions** Use the prepared mixture according to the specifications for the respective product.

**Notes** Anti-Slip Additive 150 is only suitable for single layer thicknesses < 100 µm. Anti-Slip Additive 250 is only suitable for single layer thicknesses < 200 µm. Further notes on working, system construction and maintenance of the listed products can be found in the latest Technical Data Sheets and the Remmers system recommendations.

**Storage / Shelf life** Unlimited if stored dry.



**Safety data / Regulations** Further information concerning safety during transport, storage and handling as well as on disposal and ecology can be found in the latest Safety Data Sheet.

**Disposal**



---

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.