





## **Decoflakes**

For decorative surface finishes

Colour	Availability	
	Quantity per pallet	480
	Size / Quantity	0,5 kg
	Type of container	Plastic bucket
	Container code	84
	Art. no.	
anthracite	7771	
white / grey / black / blue	7772	
white / grey / black	7773	•
white	7774	•
Application rate	Approx. 10-20 g/m² (dependent on the application)	
Range of use	■ Decorative surface finish for the Remmers 2K floor coating system and others	
Property profile	<ul><li>Highly light-fast</li><li>Weather-resistant</li><li>Single colour or multicoloured</li></ul>	
Characteristic data of the product	Bulk density	0.5-1.0 g/cm³
	Grain density	2.65 g/cm <sup>3</sup>
	Flake size	Small
	Form	Solid
	The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.	
Additional information	> Colour chart	
Application examples	Blinding material Evenly scatter the Remmers Deco Flakes onto the fresh sealant layer of the Remmers 2K floor coating by hand. For a uniform decorative finish, it is important to throw the Deco Flakes up into the air so that they are distributed uniformly and evenly across the fresh coating. On larger surfaces, it is recommended to wear spiked shoes that allow the fresh seal coat to be walked on. In addition to scattering by hand, there are also alternative application methods, e.g. using air-operated hopper guns.	
	Application rate	10-20 g/m² (depending on the application)
Notes	Further notes on working, system construction and maintenance of the listed products can be found in the latest Technical Data Sheets and the Remmers system recommendations.	
Storage / Shelf life	Unlimited if stored dry.	

Safety data / Regulations

Further information concerning safety during transport, storage and handling as well as on disposal and ecology can be found in the latest Safety Data Sheet.

ilicai Data Sheet

**Decoflakes** 





Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.