



Stopaq

Non-hardening, swellable sealant

Availability			
Quantity per pallet	48	900	
Size / Quantity		10 kg	25 x 310 ml
Type of container	Plastic bucket	cartridge	
Container code	10	25	
Art. no.			
7810	■	■	

Application rate Approx. 1.2 kg/l void



Range of use



- Non-hardening waterproofing of cables, lines and pipes
- For water loads from the rear
- Water and waste-water applications
- Sealing off water-bearing leaks

Property profile

- Impervious to pressing water up to 0.3 bar
- Gas impermeable
- Resistant to ageing
- Non-hardening
- Expands on contact with water
- Adheres to wet and dry substrates

Characteristic data of the product

Density (20 °C)	Approx. 1.2 g/cm ²
Consistency	Paste-like compound, non-hardening
Swelling properties	Approx. 10%
Colour	Greenish

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Additional information

- [Instructions for use: radon-proof wall lead-throughs](#)
- [Instructions for use](#)


Possible system products

- [Betofix R4 \(1096\)](#)
- [WP DS Levell \(0426\)](#)
- [Round Cord \(4260\)](#)

Preparation

- Substrate requirements
Clean, dust-free and capable of supporting a load.
- Substrate preparation
Roughen plastic surfaces.

Directions



- Conditions for use
Substrate temperature: +5 °C to +30 °C.
Application temperature: +10 °C to +35 °C (for the paste).
Recommended: +25 °C to +30 °C (heat the cartridge).

See instructions for use.



Tips on use

Do not use in direct contact with bituminous products.
Provide thermal insulation for lines (temp. $\geq +30$ °C).

Notes

Deviations from applicable regulations must be agreed separately.
The relevant test certificates must be observed when planning and carrying out work.

Tools / Cleaning


Sealant gun, sandpaper



Remmers tools
[▶ Dichtstoffpistole \(4701\)](#)

Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.



Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.